

加油机配件 FUEL DISPENSER COMPONENTS 电磁阀 SOLENOID VALVE

电磁阀 SOLENOID VALVE

- 内置重叠式或并联式电磁先导阀控制,工艺先进,动作可靠。
- 主阀膜片采用进口特制橡胶,强耐腐蚀,耐低温 -40 °C
- 磁路部件采用特种不锈钢磁性材料,永不生锈或产生剩磁。
- 线圈部件采用进口 F 级漆包线,使线圈温升低,绝缘性能优良。

Built-in overlapped or parallel-connected electromagnetic valve control, advanced craft and reliable action
Diaphragm of main valve has capability of anti-corrosion and resisting -40 °C low temperature
Special stainless steel magnetic material never rusts or generates remanent magnetism
Class F loop with good insulation

DSF系列

技术说明Technical Specification

Type 产品型号	DSF-20	DSF-25
介质 Medium	Gasoline , Kerosene , Diesel 汽油, 煤油, 柴油	
工作压力 Working Pressure	0.035MPa~0.35MPa	
最大流量 Max flow	3-----50L/min	80-----90L/min
工作电压 Working Voltage	AC220V AC110V DC12V DC2V	
尺寸 Diameter	20mm 3/4"	25mm G1"

MSF 系列

技术说明Technical Specification

Type 产品型号	MSF-20	MSF-25
介质 Medium	Gasoline , Kerosene , Diesel 汽油, 煤油, 柴油	
工作压力 Working Pressure	0.035MPa~0.35MPa	
最大流量 Max flow	3-----50L/min	80-----90L/min
工作电压 Working Voltage	AC220V AC110V DC24V DC12V	
尺寸 Diameter	20mm 3/4"	20mm G1"

DSF-20



MSF-20

