



■ Product Features

- Low noise, high-speed printing
- Automatic paper feeding, easy paper loading structure
- Support full cutting/half cutting
- Paper taken detection function reminder
- Auto cutter jam elimination function
- Auto cutter retraction after power on after shutdown

■ Application



ATM machine



Gas station



Vending



Charging pile



Number taking machine

product model		KP-400
Printing	Print mode	Direct Thermal
	Print width	104mm
	Print resolution	203 dpi
	Print speed max.	150mm/s
Paper	Type	Thermal receipt
	Width	118mm(standard)/114mm(Paper recycling)
	Roll paper diameter (O.D)	180mm
	Roll core inner diameter (Min.)	18mm
	Thickness	0.055-0.09mm
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24
	Code page	48
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D barcode	QR Code,PDF417
Interface	Standard	RS232+USB
	Optional	--
Sensor	Standard	Paper end, Paper near end, Paper taken
	Optional	Paper Presence
Reliability	Cutting method	Full/Partial cut
	Cutter life	1,000,000cuts
	TPH life	100km
Input Power	AC	AC100V-240V 50/60Hz
	DC	DC24V,2A
Dimensions Weight Emulation	(WxLxHmm)	175x226x118.5
	kg	1.5kg
	Commands	ESC/POS
Software	Driver	Windows Driver,Linux Driver,OPOS Driver
	SDK	Windows SDK,Android SDK,Linux SDK
Environment	Temperature	Operating:-10°C~50°C Storage:-20°C ~ 70°C
	Humidity(No condensation)	Operating:20%RH~85%RH Storage:10%~90%RH