## Product Features

- Stereoscopic and stylish appearance
- Large gears, large motor
- Large capacity supports 58mm width and 60mm diameter
- Supports 1D and 2D code printing

## Application

| Catering | Logistics | Stock Market | Retail | Cinema |
|----------|-----------|--------------|--------|--------|

| Product model | | CSN-58II | |
|---|---|---|---|
| **Printing** | Print mode | Direct Thermal | |
| | Print width | 48mm | |
| | Print resolution | 203dpi(8dots/mm) | |
| | Print speed max. | 90mm/s | |
| **Paper** | Type | Thermal receipt | |
| | Width | 58 mm | |
| | Roll paper diameter（O.D） | 60 mm | |
| | Thickness | 0.055-0.09mm | |
| **Character set** | Font | Font A:12x24;Font B:9x17  GBK:24x24 | |
| | Code page | 48 | |
| **Barocde** | 1D barocde | UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 | |
| | 2D barocde | QR Code,PDF417 | |
| **Interface** | Standard | USB+Drawer | |
| | Optional | Bluetooth | |
| **Sensor** | | Paper end | |
| **Reliability** | Cutting method | Tear bar | |
| | TPH life | 50km | |
| **Power Adapter** | AC | AC100V-240V 50/60Hz | |
| | DC | DC9V/2A | |
| | | DC12V/2A | |
| **Cashbox control** | | DC12V,1A | |
| **Dimensions** | (WxLxHmm) | 120x150x111.5mm | |
| **Weight** | kg | 0.43kg | |
| **Emulation** | Compatiable | ESC/POS | |
| **Software** | Driver | Windows Driver,Linux Driver,OPOS Driver | |
| | SDK | Windows SDK,Android SDK; Linux SDK | |
| **Environment** | Temperature | Operating:0℃~45℃ | Storage:-20℃ ~ 60℃ |
| | Humidity | Operating:20%RH~85%RH | Storage:10%~90%RH |