



■ Product Features

- High-speed printing;
- Supports 42-80mm paper width;
- Supports multiple barcode printing;
- Stylish design, compact body;
- Suitable for catering, retail, supermarkets, scenic spots and other industries

■ Application



Catering



Logistics



Scenic Spot



Medical



Cinema

Product model		CSN-310	
Printing	Print mode	Direct Thermal	
	Print width	72mm	
	Print resolution	203dpi	
	Print speed max.	200mm/s	
Paper	Type	Thermal label paper, Thermal folded paper	
	Width	76mm	
	Roll paper diameter (O.D)	50mm	
	Thickness	0.055-0.15mm	
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24	
Barcode	1D barcode	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14	
	2D barcode	QR Code,PDF417,DATAMATRIX	
Interface	Standard	USB(B type)	
	Optional	USB+Bluetooth	
Sensor		Paper end, Cover open, Gap detection	
Reliability	Cutting method	Tear off/Peel off	
	Cutter life	--	
	TPH life	50km	
Input Power	AC	AC100V-240V 50/60Hz	
	DC	DC24V,2A	
Dimensions	(WxLxHmm)	150x105x94.5mm	
Weight	kg	0.5kg	
Emulation	Commands	ESC/POS,TSPL	
Software	Driver	Windows Driver	
	SDK	K-Lalel editor,Android SDK	
Environment	Temperature	Operating:0°C~45°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:20%RH~85%RH	Storage:10%~90%RH