



■ Product Features

- Easy paper loading structure
- Low noise printing
- Rich interfaces
- Support graphic printing
- Support 60mm outer diameter printing
- Large motor, reliable and durable gears

■ Application



Test equipment



Self-service equipment



Medical equipment



Weighing scale



Self-service terminal printing

product model		EP-200
Printing	Print mode	Direct Thermal
	Print width	48 mm
	Print resolution	203dpi
	Print speed max.	100 mm/s
Paper	Type	Thermal paper
	Width	58mm
	Roll paper diameter(O.D)	60mm
	Roll core inner diameter(Min.)	9mm
	Thickness	0.055-0.09mm
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24
	Code page	48
Barcode	1D barcode	EAN-18,EAN-13,EAN-8,CODE39,CODE93,CODE128,CODABAR,ITF,UPCA,UPCB,Graphic
	2D barcode	QR Code
Interface		Parallel+RS232C+USB+Drawer
Sensor	Standard	Paper near end, Paper end
	Optional	-
Reliability	TPH life	50km
	Pulse Activation	100 Million pulse
Physical	Dimensions (WxLxH)mm	114.9x132.1x68
	Installation (WxH)mm	128x111.1
	Insert Depth size	65.4mm
	Weight	0.14kg
Emulation	Compatible	ESC/POS
Input Power	Standard	DC12V,2A
	Optional	DC9V,2A
Software	Driver	Windows Driver, Linux Driver, OPOS Driver
	SDK	Windows SDK, Android SDK, Linux SDK
Environment	Temperature	Operating:0°C~50°C Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:20%RH~85%RH Storage:10%~90%RH