



■ Product Features

- Easy paper loading structure
- Low noise printing
- Rich interfaces
- Support graphic printing
- Large motor, reliable and durable gears

■ Application



Test
equipment



Self-service
equipment



Medical
equipment



Weighing
scale



Self-service
terminal printing

product model		EP-261B
Printing	Print mode	Direct Thermal
	Print width	48 mm
	Print resolution	203dpi
	Print speed max.	80 mm/s
Paper	Type	Thermal label
	Width	25-58mm
	Roll paper diameter(O.D)	60mm
	Roll core inner diameter(Min.)	13mm
	Thickness	0.055-0.12mm
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24
	Code page	48
Barcode	1D barcode	EAN-18,EAN-13,EAN-8,CODE39,CODE93,CODE128,CODABAR,ITF,UPCA,UPCB,Graphic
	2D barcode	QR Code
Interface		RS232/TTL+USB+Drawer
Sensor		Standard Paper end, Gap detection
Reliability	TPH life	50km
	Pulse Activation	100 Million pulse
Physical	Dimensions (WxLxH)mm	95x101x69.3
	Installation (WxH)mm	90.4x96.5
	Insert Depth size	66.8mm
	Weight	0.14kg
Emulation		ESC/POS
Input Power	Standard	DC5-9V,2A
	Optional	DC12V,2A
Software	Driver	Windows Driver, Linux Driver, OPOS Driver
	SDK	Windows SDK, Android SDK, Linux SDK
Environment	Temperature	Operating: 0°C~50°C Storage: -20°C ~ 60°C
	Humidity(No condensation)	Operating: 20%RH~85%RH Storage: 10%~90%RH