



■ Product Features

- Easy paper loading structure
- Low noise printing
- Rich interfaces
- Support graphic printing
- Large motor, reliable and durable gears

■ Application



Test
equipment



Self-service
equipment



Medical
equipment



Weighing
scale



Self-service
terminal printing

product model		EP-262B	
Printing	Print mode	Direct Thermal	
	Print width	48 mm	
	Print resolution	203dpi	
	Print speed max.	80 mm/s	
Paper	Type	Thermal label	
	Width	25-58mm	
	Roll paper diameter(O.D)	60mm	
	Roll core inner diameter(Min.)	13mm	
	Thickness	0.055-0.12mm	
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24	
	Code page	48	
Barcode	1D barcode	EAN-18,EAN-13,EAN-8,CODE39,CODE93,CODE128,CODABAR,ITF,UPCA,UPCB,Graphic	
	2D barcode	QR Code	
Interface		RS232/TTL+USB+Drawer	
Sensor	Standard	Paper end, Gap detection	
Reliability	TPH life	50km	
	Pulse Activation	100 Million pulse	
Physical	Dimensions (WxLxH)mm	95x101x69.3	
	Installation (WxH)mm	90.4x96.5	
	Insert Depth size	66.8mm	
	Weight	0.14kg	
Emulation	Compatible	ESC/POS,TSPL	
Input Power	Standard	DC5-9V,2A	
	Optional	DC12V,2A	
Software	Driver	Windows Driver,Linux Driver,OPOS Driver	
	SDK	Windows SDK,Android SDK,Linux SDK	
Environment	Temperature	Operating:0°C~50°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:20%RH~85%RH	Storage:10%~90%RH