



■ Product Features

- Beautiful appearance
- Easy paper loading structure
- Low noise printing
- Rich interface
- Support graphic printing
- Front paper change, Easy loading structure
- Paper near end function

■ Application



Test
equipment



Self-service
equipment



Medical
equipment



Weighing
scale



Self-service
terminal printing

product model		EP-382C(K)
Printing	Print mode	Direct Thermal
	Print width	72mm
	Print resolution	203dpi
	Print speed max.	150mm/s 180mm/s
Paper	Type	Thermal paper
	Width	80mm
	Roll paper diameter (O.D)	80mm
	Thickness	0.055-0.09mm
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24
	Code page	48
Barcode	1D barcode	EAN-18,EAN-13,EAN-8,CODE39,CODE93,CODE128,CODABAR,ITF,UPCA,UPCB,Graphic
	2D barcode	QR Code
Interface	Standard	Serial (RS232/TTL)+USB+Drawer
Sensor	Standard	Paper end, Paper taken, Paper near end, Black mark detection Paper, Paper jam detection
Reliability	TPH life	100 km
	Cutter life	1,000,000 cuts
Physical	Dimensions (WxLxH)mm	118.7x136.1x87.5
	Installation (WxH)mm	130.7x113.3
	Insert Depth size	85mm
	Weight	0.40kg
Emulation	Compatible	ESC/POS
	Standard	DC12V,4A DC24V,2A
Input Power	Driver	Windows Driver, Linux Driver, OPOS Driver
	SDK	Windows SDK, Android SDK, Linux SDK
Software	Driver	Windows Driver, Linux Driver, OPOS Driver
	SDK	Windows SDK, Android SDK, Linux SDK
Environment	Temperature	Operating:0°C~50°C Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:20%RH~85%RH Storage:10%~90%RH