

## **■ Product Features**

- Lightweight and durable
- One-touch cover opening; OLED screen status display
- Supports multiple communication interfaces and multiple detections
- Supports label printing, as well as various blank and pre-printed ticket printing
- Removable large-capacity battery with low power consumption design, automatic sleep and automatic wake-up function
- Suitable for mobile POS, retail, parking tickets, logistics etc.

## ■ Application











Parking ticket Ship transportation Property bill On-site repair /installation

Warehousing & Logistics

product model		KLP-200
Printing	Print mode	Direct Thermal
	Print width	48mm
	Print resolution	203dpi (384dots/line)
	Print speed max.	50mm/s
Paper	Туре	Thermal label
	Width	20-58 mm
	Roll paper diameter (O.D)	50mm
	Thickness	0.05-0.15mm
Character set	Font	ASCII 9*17, 12*24, GBK:24x24
	Code page	48
Sensor		Gap detection, Paper end
Interface	Standard	Bluetooth+USB
	Optional	WIFI / NFC
Barcode	1D barcode	UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128
	2D barcode	QR Code,PDF 417
Emulation	Compatiable	ESC/POS,CPCL,TSPL
Software	Driver	Windows Driver
	SDK	Windows SDK,K-Lalel Editor,Android SDK
Battery charger	AC/DC	5V, 1A
Battery		7.4V/1600MAH
Reliability	TPH life	50km
	Pulse Activation	100 Million pulse
Physical	Dimensions (WxLxH)mm	125.8x86.6x61.3mm
	Weight	305g(with battery)
Environment	Temperature	Operating:0°C~50°C Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:10%RH~80%RH Storage:10%~90%RH