



Product Features

- Compact and lightweight design, easy to carry;
- 7.4V/1600MAH large capacity;
- Various interfaces;
- Automatic sleep/automatic wake-up to save energy and extend usage time;
- Support multiple languages.

Application



Parking
ticket



Ship
transportation



Property
bill



On-site repair
/installation



Warehousing
& Logistics

product model		KMP-200	
Printing	Print mode	Direct Thermal	
	Print width	48mm	
	Print resolution	203dpi	
	Print speed max.	90mm/s	
Paper	Type	Thermal receipt	
	Width	58 mm	
	Roll paper diameter (O.D)	50mm	
	Thickness	0.055-0.09mm	
Character set	Font	ASCII 9*17、12*24、GBK:24*24	
	Code page	48	
Sensor		Paper end	
Interface	Standard	Bluetooth+USB	
	Optional	WIFI / NFC	
Barcode	1D barcode	UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128	
Emulation	2D barcode	QR Code,PDF417	
	Compatible	ESC/POS	
Software	Driver	Windows Driver,Linux Driver	
	SDK	Windows SDK,Android SDK,Linux SDK	
Battery charger	AC/DC	5V, 1A	
Battery		7.4V/1600MAH	
Reliability	TPH life	50km	
	Pulse Activation	100 Million pulse	
Physical	Dimensions (WxLxH)mm	125.8x86.6x61.3mm	
	Weight	305g(with battery)	
Environment	Temperature	Operating:-5°C~50°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:20%RH~80%RH	Storage:10%~90%RH