



■ Product Features

- Lightweight design, easy to carry
- Large capacity battery
- Auto sleep/auto wake-up
- Printer head overheat protection
- Paper end detection

■ Application



Parking
ticket



Ship
transportation



Property
bill



On-site repair
/installation



Warehousing
& Logistics

product model		KMP-III	
Printing	Print mode	Direct Thermal	
	Print width	72mm	
	Print resolution	203dpi(576dots/line)	
	Print speed max.	90 mm/s	
Paper	Type	Thermal paper	
	Width	80 mm	
	Roll paper diameter (O.D)	50 mm	
	Thickness	0.055-0.09mm	
Character set	Font	Font A:12x24; Font B:9x17 GBK:24x24	
	Code page	48	
Sensor		Paper end	
Interface	Standard	Bluetooth+USB	
	Optional	WIFI,RS232C	
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
	2D barcode	QR Code	
Emulation	Compatible	ESC/POS	
Software	Driver	Windows Driver,Linux Driver,OPOS Driver	
	SDK	Windows SDK,Android SDK, IOS SDK	
Battery charger Battery	AC/DC	5V, 1A	
		7.4V Li-ion,2600mAh, 4.0Hrs Charging time	
Reliability	TPH life	50km	
	Pulse Activation	100 Million pulse	
Physical	Dimensions (WxLxH)mm	99x127x55.5mm	
	Weight	305g(with battery)	
Environment	Temperature	Operating:0°C~50°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:10%RH~80%RH	Storage:10%~90%RH