



■ Product Features

- Lightweight design, easy to carry
- Supports thermal paper/thermal label paper roll printing
- One-touch cover opening, OLED display
- Supports Bluetooth/dual-mode Bluetooth+USB
- Auto sleep/auto wake

■ Application



Parking
ticket



Ship
transportation



Property
bill



On-site repair
/installation



Warehousing
& Logistics

product model		PLP-III	
Printing	Print mode	Direct Thermal	
	Print width	72 mm	
	Print resolution	203dpi(576dots/line)	
	Print speed max.	60mm/s	
Paper	Type	Thermal paper/Thermal label	
	Width	80mm	
	Roll paper diameter (O.D)	40mm	
	Thickness	0.055-0.15mm	
Character set	Font	ASC II :9x17,9x24,16x18,12x24, GBK:24x24	
	Code page	48	
Sensor		Paper end, Gap detection	
Interface	Standard	Bluetooth+USB	
	Optional	WIFI	
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
	2D barcode	QR Code,PDF 417	
Emulation	Compatiable	ESC/POS,CPCL,TSPL	
Software	Driver	Windows Driver	
	SDK	K-Lalel Editor,Windows SDK ,Android SDK	
Battery charger Battery	AC/DC	5V,1A	
		7.4V Li-ion, 1500mAh/2000mAh 3.0/3.5Hrs Charging time	
Reliability	TPH life	50km	
	Pulse Activation	100 Million pulse	
Physical	Dimensions (WxLxH)mm	111x124x48mm	
	Weight	360g(with battery)	
Environment	Temperature	Operating:0°C~50°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:10%RH~80%RH	Storage:10%~90%RH