



电机规格说明 SPECIFICATION

相数 number of phase	2	绝缘耐压 DIELECTRIC STRENGTH	500
步距角 STEP ANGLE	1.8°	绝缘电阻 INSULATION RESISTANCE	100MΩ/min
步距角误差 Position Accuracy		绝缘等级 INSULATION CLASSE (UL)	B
相额定电流 Rated Current/phase	4.0A	温升 Temperature Rise Max	80
相电阻 RESISTANCE/phase:	0.8Ω±10%	使用温度范围 Working Ambient Temperature	0 ~ 50° C
相电感 INDUCTANCE/PHASE:	3.2 MH±20%	使用湿度范围 Working Ambient Humidity	20% ~ 90%RH
静力矩 HOLDING TORQUE:	3.3 N.m	保存温度范围 Storage Ambient Temperature	-20 ~ 70° C
转子惯量 Rotate Interia	950g.cm²	保存湿度范围 Storage Ambient Humidity	15% ~ 90%RH

		产品系列				
		产品名称				
		投影方式	产品型号	60J18100-440-8F		
				签名	日期	
绘图	何成威	2023/5/23	标准化			
设计			工艺			
校准			审批			
				单位	比例	重量/kg
				mm	1: 1	页数
						版本
				mm	1: 1	第张共张
						A

深圳市杰美康机电有限公司
Shenzhen Just Motion Control
Electromechanics Co., LTD



公司网址 www.jmc-motion.com