

GP Series General AGM Battery

12V 7AH-250AH



Performance Characteristics

- Using tight assembly technology with excellent high efficiency discharge performance
- With special design, the battery will not reduce the amount of electricity fluid during use, even no necessary to add any water during using life time
- Uses a unique corrosion-resistant grid alloy, long service life
All with high purity raw materials, battery self-discharge is minimal
- Using gas compounds technology, the battery has a high sealing reaction efficiency, no mist precipitation, safety and environmental protection, pollution-free
- With special design and high reliable sealing technology to ensure the battery sealing, safe, and reliable

Applied Range

UPS System, EPS System, Solar & Wind Power Generation System, Emergency Lighting System, Electrical Power System, Signal System, Communication System, Data Center

Technical Specifications

Model	Nominal Voltage (V)	Capacity (Ah)	Length	Width	Height	Total Height	Weight (Kg)	Terminal	Layout
GP7-12	12	7/20HR	151	65	94	100	2.13	F2	D
GP7.5-12	12	7.5/20HR	151	65	94	100	2.2	F2	D
GP8.5-12	12	8.5/20HR	151	65	94	100	2.4	F2	D
GP10-12	12	10/20HR	152	99	96	102	3.15	F2	D
GP12-12	12	12/20HR	152	99	96	102	3.38	F2	D
GP17-12	12	17/20HR	181	77	167	167	5.18	L1	B
GP20-12	12	20/20HR	181	77	167	167	6	L1	B
GP24-12AQ	12	24/10HR	165	126	174	179	7.7	L6	B



Technical Specification

Model	Nominal Voltage (V)	Capacity (Ah)	Length	Width	Height	Total Height	Weight (Kg)	Terminal	Layout
GP24-12AT	12	24/10HR	165	126	174	174	7.7	T2	B
GP26-12AT	12	26/10HR	166	175	126	126	8.3	T2	B
GP33-12AQ	12	33/10HR	196	130	155	179	10	L7	A
GP33-12AT	12	33/10HR	196	130	155	176	10	T2	A
GP38-12AQ	12	38/10HR	197	166	174	179	12.3	L6	B
GP38-12AT	12	38/10HR	197	166	174	174	12.3	T2	B
GP42-12AQ	12	42/10HR	198	166	174	174	12.9	L7	B
GP42-12AT	12	42/10HR	198	166	174	174	12.9	T2	B
GP50-12AQ	12	50/10HR	258	134	200	200	15.5	L8	A
GP50-12BT	12	50/10HR	229	138	208	212	15.8	T3	A
GP55-12AP	12	55/10HR	229	138	208	226	16.3	L4	A
GP55-12AT	12	55/10HR	229	138	208	212	16.3	T3	A
GP65-12AQ	12	65/10HR	350	167	178	178	20.2	L9	B
GP65-12AT	12	65/10HR	350	167	178	178	20.2	T3	B
GP70-12AQ	12	70/10HR	350	167	178	178	21.3	L9	B
GP70-12AT	12	70/10HR	350	167	178	178	21.3	T3	B
GP80-12AQ	12	80/10HR	331	174	214	240	24.8	L12	B
GP80-12AT	12	80/10HR	331	174	214	219	24.8	T4	B
GP90-12AQ	12	90/10HR	307	169	211	227	26.5	L13	A
GP90-12AT	12	90/10HR	307	169	211	215	26.5	T3	A
GP100-12AQ	12	100/10HR	331	174	214	240	29.0	L12	B
GP100-12AT	12	100/10HR	331	174	214	219	29.0	T4	B
GP120-12AQ	12	120/20HR	331	174	214	240	32.3	L12	B
GP120-12AT	12	120/20HR	331	174	214	219	32.3	T4	B
GP150-12AQ	12	150/20HR	484	171	241	241	43.5	L15	A
GP150-12AT	12	150/20HR	484	171	241	241	43.5	T4	A
GP160-12AQ	12	160/10HR	532	206	216	240	48.3	L17	C
GP160-12AT	12	160/10HR	532	206	216	221	48.3	T4	C
GP180-12AQ	12	180/10HR	532	206	216	240	55.0	L17	C
GP180-12BT	12	180/10HR	532	206	216	221	52.2	T4	C
GP200-12AQ	12	200/10HR	522	240	219	244	58.2	L17	C
GP200-12AT	12	200/10HR	522	240	219	224	58.2	T5	C
GP220-12AQ	12	220/10HR	522	240	219	244	60.5	L17	C
GP220-12AT	12	220/10HR	522	240	219	224	60.2	T5	C
GP250-12AQ	12	250/10HR	520	268	220	245	70.0	L17	C
GP250-12AT	12	250/10HR	520	268	220	225	70.0	T5	C