

GPDG Series Deep Cycle Gel Battery

12V 24AH-260AH



Performance Characteristics

- High Quality Fumed silica gel preparation, uniform distribution of electrolyte, acid stratification does not exist
- Electrolyte gel was fixed state, no flow, no leakage, so that all parts of the plate uniform reaction
- Radial grid design, a tight assembly technology with excellent high efficiency discharge performance
- Deep cycle battery design, using 4BS lead paste technology, cycle use has long service life
- All with high purity raw materials, battery self-discharge is minimal
- Using gas compounds technology, the battery has a high sealing reaction efficiency, no mist precipitation, safety and environmental protection, pollution-free
- With special design and high reliable sealing technology to ensure the battery sealing, safe and reliable

Applied Range

Solar & Wind Power Generation System, UPS System, EPS System, Electrical Power System, Communication System, Emergency Lighting System, Signal System, Data Center

Technical Specification

Model	Nominal Voltage (V)	Capacity (Ah)	Length	Width	Height	Total Height	Weight (Kg)	Terminal	Layout
GPDG24-12	12	24/20HR	166	175	126	126	8.4	T2	B
GPDG26-12	12	26/20HR	165	126	174	179	8.5	T2	B
GPDG35-12	12	35/20HR	196	130	155	167	10.6	T2	A
GPDG35-12	12	35/20HR	196	130	155	167	10.6	T2	B
GPDG40-12	12	40/20HR	198	166	174	174	14.3	T2	B
GPDG70-12	12	70/20HR	350	167	178	178	23.4	T3	A
GPDG75-12	12	75/20HR	260	169	211	215	25.1	T3	A
GPDG85-12	12	85/20HR	260	169	211	215	26.2	T3	B
GPDG90-12	12	90/20HR	307	169	211	216	28.3	T3	A
GPDG100-12	12	100/20HR	307	169	211	216	30.3	T3	A
GPDG110-12	12	110/20HR	331	176	214	220	33.5	T3	A
GPDG120-12	12	120/20HR	407	173	210	233	39.5	T4	B
GPDG135-12	12	135/20HR	341	173	283	288	41.0	T5	A
GPDG150-12	12	150/20HR	484	171	241	241	45.7	T4	A
GPDG180-12	12	180/20HR	532	206	216	222	56.2	T4	C
GPDG200-12	12	200/20HR	532	206	216	222	58.6	T4	C
GPDG220-12	12	220/20HR	522	240	219	225	65.2	T5	C
GPDG260-12	12	260/20HR	520	268	220	226	77.3	T5	C