

H181

一层钢丝编织管

ISO 1436 TYPE 1SN / SAE 100R1 TYPE AT/DIN EN 853 TYPE 1SN

# 型号	 软管内径 I.D.				 软管外径	 最大工作压力		 最小弯曲半径	 重量
	DN	inch	Size	mm	mm	MPa	psi	mm	kg/m
481-4	6	1/4	-4	6.3	13.4	22.5	3250	50	0.24
481-5	8	5/16	-5	8	15	22.5	3250	55	0.27
481-6	10	3/8	-6	10	17.4	20.7	3000	65	0.34
481-8	12	1/2	-8	12.5	20.7	17.2	2500	90	0.43
481-10	16	5/8	-10	16	23.9	13.8	2000	100	0.49
481-12	19	3/4	-12	19	27.8	12.0	1750	120	0.63
481-16	25	1	-16	25	35.8	8.8	1275	150	0.94
481-20	31	1-1/4	-20	31.5	45.3	6.3	910	210	1.19
481-24	38	1-1/2	-24	38	50.8	5.0	725	250	1.49
481-32	51	2	-32	51	64.7	4.0	575	315	2.23

适用介质: 石油基液压油, 水乙二醇, 润滑油, 空气和水。用于1.7MPa以上的空气时, 软管需针刺。

内胶层: 合成橡胶

增强层: 一层钢丝编织

外胶层: 合成橡胶

温度范围: -40 °C 至 +100 °C

除: 空气: 最高 +70 °C
 水: 最高 +85 °C