

H381

两层钢丝编织管

ISO 1436 TYPE 2SN / SAE 100R2 TYPE AT/ DIN EN 853 TYPE 2SN

# 型号	 软管内径 I.D.				 软管外径	 最大工作压力		 最小弯曲半径	 重量
	DN	inch	Size	mm	mm	MPa	psi	mm	kg/m
381-4	6	1/4	-4	6.3	15	40.0	5800	100	0.39
381-5	8	5/16	-5	8	16.6	36.0	5250	115	0.42
381-6	10	3/8	-6	10	19	35.0	5000	125	0.55
381-8	12	1/2	-8	12.5	22.2	29.7	4250	180	0.67
381-10	16	5/8	-10	16	25.4	25.0	3625	200	0.77
381-12	19	3/4	-12	19	29.3	21.5	3125	240	1.00
381-16	25	1	-16	25	37.8	17.5	2500	300	1.49
381-20	31	1-1/4	-20	31.5	47.5	15.7	2250	420	2.16
381-24	38	1-1/2	-24	38	55	12.5	1800	500	2.73
381-32	51	2	-32	51	67	9.0	1300	630	3.35

适用介质:石油基液压油, 水乙二醇, 润滑油, 空气和水。用于1.7MPa以上的空气时, 软管需针刺。

内胶层:合成橡胶

增强层:两层钢丝编织

外胶层:合成橡胶

温度范围: -40°C 至 +100 °C

除: 空气: 最高 +70 °C

水: 最高 +85 °C